

we care 

primus

laundry equipment

## High Spin Industrial Washer Extractors

FS 33, FS 40, FS 55



### FEATURES

- Freestanding, high spin
- Stainless steel cabinet (AISI 304)
- Stainless steel drum and tub
- Graphitronic® - new graphic display with almost unlimited possibilities as:
  - Communication interface enabling remote service
  - Multilingual microprocessor
  - Freely programmable
- Large door opening (Ø53 cm) for easy loading and unloading
- Large drain valves (2xØ76 mm)
- Easy access to all parts
- Standard liquid soap connections
- Frequency controlled motor
- Patented soap dispenser with 5 removable compartments
- PowerWash® perforated lifting ribs: more mechanical action, lower water consumption
- SuperEco washing programmes
  - significantly reduces water and electricity consumption

### OPTIONS

- Low steam pressure heating
- Liquid soap pumps
- SoftWash® version (wet cleaning)
- Trace-Tech® traceability software and networking system



ROBUST DESIGN



EXTRA LARGE DOOR



LARGE DRAIN VALVE

POWERWASH®

supereco

Graphitronic®

TRACE-TECH




TYPE		FS 33	FS 40	FS 55
<b>CAPACITY</b>				
Drum volume	l	335	400	518
Capacity	kg/lb	33/80	40/100	55/125
Drum diameter	mm	Ø914	Ø914	Ø914
<b>MOTOR</b>				
Frequency controlled		standard	standard	standard
<b>DRUM SPEED</b>				
Wash speed	rpm	38	38	38
Spin speed	rpm	830	830	830
G-Factor		350	350	350
<b>PROGRAMMER</b>				
Graphitronic® microprocessor		standard	standard	standard
<b>CABINET</b>				
Stainless steel AISI 304		standard	standard	standard
SAFETY FIXING		yes (4xM16)	yes (4xM16)	yes (4xM16)
<b>HEATING</b>				
100% hot water	° C	90	90	90
	° F	194	194	194
100% electrical	kW	24	36	54
Steam high pressure	bar	3-8	3-8	3-8
<b>CONNECTION</b>				
Electrical		3x220-240V 50/60Hz 3x380-480V 50/60Hz Others on request		
Water inlet	inch	1"		
Steam inlet	inch	3/4"		
<b>DIMENSIONS</b>				
HxWxD	mm	1905x1195x1330	1905x1195x1430	1905x1195x1610
<b>TRANSPORT DATA</b>				
Gross weight				
Crate packing	kg	1370	1700	1770
Net weight	kg	1230	1560	1630
Volume (packed)				
Crate packing	m <sup>3</sup>	4,4	4,7	5,3
Crate packing HxWxD	mm	2105x1430x1475	2105x1430x1570	2105x1430x1750
<b>WATER CONSUMPTION</b>				
Cold and hot water per cycle*	l	202 + 50	445 + 79	528 + 93

Standard = Standard version, \* Tested in accordance of EN 604 56 norm  
The data concerning dimensions of machines include all extended parts

FRONT FS 33 40 55

SIDE FS 33 40 55

BACK FS 33 40 55



1. Soap hopper
2. Keyboard
3. Keypad
4. Emergency stop
5. Electrical connection
6. Electrical connection to liquid soap
7. Main switch
8. Liquid soap pump connections
9. Air vent tub
10. Water connection
11. Drain valve

10 - 2009 / 532 480

The company Primus preserves the right to change the machines and the specification in this leaflet at any time, without prior notice. Details and photographs are only for information and never binding.

[www.primuslaundry.com](http://www.primuslaundry.com)

ISO 9001  
ISO 14001  
BUREAU VERITAS  
Certification

